

TOPOGRAPHY

DEPARTMENT OF THE INTERIOR
ALBERT B. FALL, SECRETARY
U. S. GEOLOGICAL SURVEY
GEORGE OTIS SMITH, DIRECTOR

STATE OF NEW YORK
FRANK M. WILLIAMS
STATE ENGINEER AND SURVEYOR

STATE OF PENNSYLVANIA
DEPARTMENT OF INTERNAL AFFAIRS
JAMES F. WOODWARD, SECRETARY
BUREAU OF TOPOGRAPHIC AND GEOLOGICAL SURVEY
GEORGE H. ASHLEY, STATE GEOLOGIST

NEW YORK-PENNSYLVANIA
WHITE LAKE QUADRANGLE



U. S. G. S.
FILE COPY
Inspection and Editing.

U. S. G. S.
FILE COPY
Inspection and Editing.

41°30' 75°00'
1820000 YARDS ENGRAVED 1922 BY U.S.G.S.
C. H. Birdseye, Chief Topographic Engineer.
Frank Sutton, Topographic Engineer in charge.
Topography by H. H. Hodgeson, R. L. McCammon,
H. E. Simmons, E. B. Hill, and E. V. Holloway.
Control by Geo. T. Hawkins, H. H. Hodgeson,
R. G. Clinite, and G. M. Dimmick.
Surveyed in 1920.

Scale 62500
1 2 3 4 Miles
1 2 3 4 5 Kilometers
Contour interval 20 feet.
Datum is mean sea level.

Polyconic projection, North American datum.
5000 yard grid based upon U.S. zone system, A.
THROUGH ROUTES (STANDARD) ———
THROUGH ROUTES (NOT STANDARD) ———
SECONDARY ROUTES - - - - -
CAPACITY OF BRIDGES (5 TO 15 TONS) SHOWN BY RED FIGURES
USGS
Historical File
Topographic Division
JAN 5 1923
WHITE LAKE, N.Y. - PA.
Edition of 1922.