



Control by USC&GS, USGS, and TVA
Topography by Geological Survey from aerial
photographs by stereophotogrammetric methods
Field examination by Tennessee Valley Authority, 1941

UTM GRID AND 1941 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET

SCALE 1:24,000
CONTOUR INTERVAL 20 FEET
DATUM IS MEAN SEA LEVEL

ROUTES USUALLY TRAVELED
HARD IMPERVIOUS SURFACES
OTHER SURFACE IMPROVEMENTS
U.S. ROUTE
STATE ROUTE

Polycyclic projection. 1927 North American datum
10,000-foot grid based on Tennessee
rectangular coordinate system
1000-meter Universal Transverse Mercator grid ticks,
zone 17, shown in blue

DUTCH VALLEY, TENN.
154-SE
N3615-W8330/7.5
1941
AMS 4256 1 SE-SERIES B841

FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D. C. 20242,
U.S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.,
AND TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENNESSEE
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

U.S.G.S.
HISTORICAL FILE
TOPOGRAPHIC DIVISION
AUG 5 1985