



Mapped and edited by Tennessee Valley Authority
Published by the Geological Survey


Basic control by USCGS, USGS, and TVA

Topography by USGS and TVA by multiplex and planetable
methods. Aerial photographs taken 1946
Field examination by TVA, 1949

Polyconic projection. 1927 North American datum
10,000-foot grid based on Tennessee rectangular
coordinate system

—374—Indicates Kentucky Lake Easement Boundary

TRUE NORTH
MAGNETIC NORTH
APPROXIMATE MEAN
DECLINATION 1949



CONTOUR INTERVAL 20 FEET

DASHED LINES REPRESENT HALF-INTERVAL CONTOURS
DATUM IS MEAN SEA LEVEL

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS

FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.

TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENNESSEE

U. S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.

A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
HISTORICAL FILE
TOPOGRAPHIC DIVISION

U. S. G. S.
FILE COPY

ROAD CLASSIFICATION
HARD-SURFACE ALL WEATHER ROADS DRY WEATHER ROADS
Heavy-duty ———— LANE 6 LANE Improved dirt ————
Medium-duty ———— LANE 6 LANE Unimproved dirt ————
Loose-surface, graded, or narrow hard-surface ————
④ U. S. Route ② State Route

HOOKERS BEND, TENN.
N3515-W8807.5/7.5

1949