





Mapped and edited by Tennessee Valley Authority
Published by the Geological Survey
Control by US&GS, USGS, and TVA

Topography by USGS and TVA by multiplex methods from aerial
photographs taken 1947. Field examination by TVA, 1950
Polyconic projection, 1927 North American datum
10,000-foot grid based on Tennessee rectangular
coordinate system

— 380 — Indicates Kentucky Lake Easement Boundary

4°
TRUE NORTH
MAGNETIC NORTH
APPROXIMATE MEAN
DECLINATION 1950



CONTOUR INTERVAL 20 FEET
DASHED LINES REPRESENT HALF-INTERVAL CONTOURS
DATUM IS MEAN SEA LEVEL
THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.
TENNESSEE DIVISION OF GEOLOGY, NASHVILLE, TENN.
U. S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
HISTORICAL FILE
TOPOGRAPHIC DIVISION

ROAD CLASSIFICATION
HARD-SURFACE ALL WEATHER ROADS DRY WEATHER ROADS
Heavy-duty — 2 LANE 18 LANE Improved dirt —
Medium-duty — 2 LANE 18 LANE Unimproved dirt —
Loose surface, graded, or narrow hard-surface —
U. S. Route State Route

HURRICANE MILLS, TENN.
N3552.5-W8745/7.5

1950
MINOR CORRECTIONS MADE 1951

APR 24 1953