SHIPROCK

Prepared by the U.S. Army Topographic Command (BESX), Washington, D.C. Compiled in 1955 by photogrammetric methods from aerial photographs taken 1954. Photographs field annotated 1954. Revised by the U.S. Geological Survey 1969.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES: LOS ANGELES; OMAHA; GALVESTON; Laramie; Grand Coulee; Sun Valley

RAILROADS: Standard gauge; Narrow gauge; Single track; Double or Multiple

BOUNDARIES: International; State; County; Park or reservation

Landplane airport; Landing area; Seaplane airport; Seaplane anchorage; Woods-brushwood

Windmill; Mine; Landmark: School; Church; Other; Spot elevation in feet; Marsh or swamp; Intermittent or dry stream; Power line

ROADS: Primary, all-weather, hard surface; Secondary, all-weather, hard surface; Light-duty, all-weather, hard or improved surface; Fair or dry weather, unimproved surface; Trail; Interchange

Route markers: Interstate, U.S., State

Scale 1:250,000

5 0 5 10 15 20 Statute Miles

5 0 5 10 15 20 25 30 Kilometers

5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 200 FEET

WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 12

1965 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 14½° (260 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 13½° (240 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092

LOCATION DIAGRAM



SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

TOWNSHIP OR RANGE LINE

LAND GRANT BOUNDARY

GRID ZONE DESIGNATION: 12S

100,000 M. SQUARE IDENTIFICATION

WR	XR	YR
WQ	XQ	YQ

400 / 40 / 70

IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figures of the grid number; example: 39Q0000 E

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: RED ROCK

1. Read letters identifying 100,000 meter square in which the point lies:
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either on the top or bottom margin, or on the line itself.
   Estimate tenths from grid line to point:
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself.
   Estimate tenths from grid line to point:

SAMPLE REFERENCE:	XR7352	
If reporting beyond 10° in any direction, prefix Grid Zone Designation, as:	12SXR7352	

SHIPROCK, N. MEX.; ARIZ.; COLO.; UTAH

1954

REVISED 1969

USGS MAP LIBRARY
SHIPROCK NEW MEXICO
TO RETURN
8818