



Mapped, edited, and published by the Geological Survey
Control by USGS and USC&GS
Topography from aerial photographs by photogrammetric methods
Aerial photographs taken West Virginia 1956, and Ohio 1958
Field check West Virginia 1958, and Ohio 1960
Polyconic projection. 1927 North American datum
10,000-foot grids based on Ohio coordinate system, south zone,
and West Virginia coordinate system, south zone
1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue
Fine red dashed lines indicate selected fence and field lines where
generally visible on aerial photographs. This information is unchecked
The state boundary as shown represents the approximate position of the low
water line as determined from U. S. Corps of Engineers, Ohio River charts,
surveyed 1913, and supplementary information
Land lines based on the Ohio River Base. Dotted land lines established
by private subdivision of the Ohio Company Purchase

UTM GRID AND 1975 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET

SCALE 1:24,000
CONTOUR INTERVAL 20 FEET
DOTTED LINES REPRESENT 10 FOOT CONTOURS
NATIONAL GEODETIC VERTICAL DATUM OF 1929

ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt ———
U. S. Route ——— State Route ———

QUADRANGLE LOCATION
OHIO

Revisions shown in purple compiled in cooperation with
State of Ohio agencies from aerial photographs taken
1971 and 1975. This information not field checked

USGS
Historical File
Topographic Division

1960
PHOTOREVIEWED 1971 AND 1975
AMS 4562 II SE-SERIES V852

POMEROY, OHIO-W. VA.
N3900-W8200/7.5

APR 12 1977

5650