





Mapped, edited, and published by the Geological Survey
Revised in cooperation with State of Ohio agencies
Control by USGS and NOS/NOAA
Topography by planetable surveys 1934. Revised 1965
Selected hydrographic data compiled from U. S. Lake Survey chart 374 (1965)
This information is not intended for navigational purposes
Polyconic projection. 10,000-foot grid based on Ohio coordinate system, north zone. 1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue. 1927 North American Datum To place on the predicted North American Datum 1983 move the projection lines 1 meter south and 6 meters west as shown by dashed corner ticks
Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked
Red tint indicates areas in which only landmark buildings are shown
Land lines north of the Fulton Line based on the Michigan Meridian
Land lines south of the Fulton Line based on the First Principal Meridian

UTM GRID AND 1980 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET



FOR SALE BY U. S. GEOLOGICAL SURVEY
DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt ———
Interstate Route ——— U. S. Route ——— State Route ———

Revisions shown in purple compiled in cooperation with State of Ohio agencies from aerial photographs taken 1977 and other source data. This information not field checked. Map edited 1980
Purple tint indicates extension of urban areas

ROSSFORD, OHIO
41083-E5-TF-024
1965
PHOTOREVISED 1980
DMA 4267 II SE—SERIES V852

USGS NMD HISTORICAL MAP
SEP 12 1988
REC'D FILE COPY