



Mapped, edited, and published by the Geological Survey
Control by USGS and NOS/NOAA
Topography by photogrammetric methods from aerial photographs taken 1976. Field checked 1977. Revised 1981
Polyconic and 10,000-foot grid ticks: Utah coordinate system south zone (Lambert conformal conic)
1000-meter Universal Transverse Mercator grid ticks, zone 12. The difference between 1927 North American Datum and North American Datum of 1983 NAD 83 for 7.5 minute intersections is given in USGS Bulletin 1875. The NAD 83 is shown by dashed corner ticks
Fine red dashed lines indicate selected fence lines
Areas covered by dashed light-blue pattern are subject to controlled inundation
There may be private inholdings within the boundaries of the National or State reservations shown on this map

UTM GRID AND 1981 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

0°20' 6 MILLS
14° 249 MILLS

SCALE 1:24 000

1 1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 5 0 1 KILOMETER

CONTOUR INTERVAL 40 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929

ROAD CLASSIFICATION

Primary highway, hard surface
Secondary highway, hard surface
Unimproved road
Light-duty road, hard or improved surface
Unimproved road

Interstate Route
U. S. Route
State Route

UTAH

QUADRANGLE LOCATION

USGS HISTORICAL MAP
MAR 07 1991
REC'D FILE COPY

LONE ROCK, UTAH-ARIZ.

37111-A5-TF-024
1981
DMA 3658 II SE-SERIES Y897