




Mapped, edited, and published by the Geological Survey
in cooperation with the Bureau of Reclamation
Control by USGS, USC&GS, and USBR
Topography by photogrammetric methods from aerial
photographs taken 1964 and planetable surveys by USBR 1955
Field checked 1965

Polyconic projection. 1927 North American Datum
10 000-foot grid based on Utah coordinate system, central zone
1000-meter Universal Transverse Mercator grid ticks,
zone 12, shown in blue

Fine red dashed lines indicate selected fence lines

Map photosinspected 1978
No major culture or drainage changes observed

To place on the predicted North American Datum 1983
move the projection lines 8 meters north and
59 meters east as shown by dashed corner ticks



CONTOUR INTERVAL 20 FEET
DOTTED LINES REPRESENT 10-FOOT CONTOURS
DOTTED LINES CROSSING RIVERS REPRESENT 5-FOOT CONTOURS
NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Unimproved dirt ———
U. S. Route ——— State Route ———

RASMUSSEN HOLLOW, UTAH
40109-C4-TF-024

1965
PHOTOINSPECTED 1978
DMA 4164 IV SW-SERIES V897

