UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

DE TOUR VILLAGE QUADRANGLE
MICHIGAN—CHIPPEWA CO.
7.5 MINUTE SERIES (TOPOGRAPHIC)

4276 II SE (GOETZVILLE)
4276 III SE (BURNT ISLAND)
4276 III SW (LIME ISLAND)
4175 I NE (ALBANY ISLAND)
4275 IV NE (WHITNEY BAY)

84°00′ 46°00′ 83°52′30″ 45°52′30″
268 000m E. 270 57′30″ 272 273 274 55′ 275 440 000 FEET 276 277
5098 000m N. 5096 5095 5094 5093 5092 5090 5089 5088 5087 5086 5085 5084 000m N.
1 600 000 FEET
1 630 000 FEET

5 MI. TO MICH. 48
3.7 MI. TO MICH. 48
CEDARVILLE 20 MI.
42 MI. TO MICH. 48
LINCOLN 12 MI.

Caribou Lake
Brown Lake
Bear Lake
Caribou Creek
Hartley Lake
Gravel Pit
Sandpit
Maple Grove Cem
De Tour Village (De Tour)
BOUNDARY
CORPORATE
SOUTH
ROAD
NORTH
BM 637
BM 597
BM 607
BM 613
Substation
Lighthouse
Frying Pan Island
Frying Pan Shoal
FERRY
Bob Hill Cem
Radio Tower
Olmstad Bay
Roggs Bay
Gut Port
Seymour Bay
Strawberry Island
Carlton Bay
Bennett Point
Peters Island
Rice Point
Crow Island
De Tour Shoal
Point De Tour
De Tour Lighthouse
Barbed Point
Crab Island
Crab Island Shoal
Jones Island
Light 8
Quarry
DE TOUR STATE PARK
ST VITAL BAY
St Vital Point
ST VITAL SHOAL
MUNUSCONG STATE FOREST
DRUMMOND ISLAND TWP MUNUSCONG STATE FOREST
DE TOUR
SAINT MARYS RIVER PASSAGE
T. 42 N.
T. 41 N.
R3E R4E
1 2 3 4 5 6 7 8 9 10 12 13 15

LAKE HURON
APPROXIMATE MEAN LAKE ELEVATION 580

Mapped, edited, and published by the Geological Survey

Control by USGS, USC&GS, and U. S. Lake Survey

Topography by photogrammetric methods from aerial photographs taken 1954–55. Field checked 1964

Selected hydrographic data compiled from U. S. Lake Survey Chart 61 (1961). This information is not intended for navigational purposes

Polyconic projection. 1927 North American datum
10,000-foot grid based on Michigan coordinate system, east zone
1000-meter Universal Transverse Mercator grid ticks, zone 17, shown in blue

Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked

MN
GN
4½° 80 MILS
2°07′ 38 MILS
UTM GRID AND 1964 MAGNETIC NORTH DECLINATION AT CENTER OF SHEET

SCALE 1:24 000
1 0 1 MILE
1000 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 5 0 1 KILOMETER
CONTOUR INTERVAL 10 FEET
DATUM IS MEAN SEA LEVEL
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS LOW WATER 578.5 FEET

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON, D. C. 20242
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
Historical File
Topographic Division

MICHIGAN
QUADRANGLE LOCATION

ROAD CLASSIFICATION
Medium-duty
Light-duty
Unimproved dirt
State Route

DE TOUR VILLAGE, MICH.
N4552.5—W8352.5/7.5
1964
AMS 4275 IV NW—SERIES V862

2945
JAN 21 1966
U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

INTERIOR—GEOLOGICAL SURVEY, WASHINGTON, D. C.—1965