



Produced by the United States Geological Survey

Control by USGS and NOS/NOAA



Topography by photogrammetric methods from aerial photographs taken 1958. Revised from aerial photographs taken 1983 and 1985. Field checked 1988. Map edited 1989.

Projection and 10,000-foot grid ticks: Michigan coordinate system, central zone (Lambert conformal conic). 1000-meter Universal Transverse Mercator grid, zone 17 1927 North American Datum.

To place on the predicted North American Datum 1983, move the projection lines 2 meters north and 4 meters west as shown by dashed corner ticks.

There may be private inholdings within the boundaries of the National or State reservations shown on this map.

Fine red dashed lines indicate selected fence and field lines where generally visible on aerial photographs. This information is unchecked.



SCALE 1:24 000

CONTOUR INTERVAL 10 FEET  
NATIONAL GEODETIC VERTICAL DATUM OF 1929

THIS MAP COMPLETES WITH NATIONAL MAP ACCURACY STANDARDS  
FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092  
AND GEOLOGICAL SURVEY DIVISION  
MICHIGAN DEPARTMENT OF NATURAL RESOURCES, LANSING, MICHIGAN 48909  
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION  
Primary highway, hard surface .....  
Secondary highway, hard surface .....  
Unimproved road .....  
Interstate Route .....  
U. S. Route .....  
State Route .....



QUADRANGLE LOCATION

FLOYD LAKE, MICH.  
SW/4 TAWAS CITY 15' QUADRANGLE  
44083-C6-TF-024

1989  
DMA 4272 1 SW - SERIES V862

