




Mapped by the Geological Survey
1946

Road Classification
1947
Dependable hard-surface
Heavy-duty road
Secondary hard-surface
at weather road
More than two lanes indicated along road with tick at point of change
Dry-weather roads
Unsurfaced, graded
Dirt road
State Route (16)
U.S. Route (16)

UTM GRID AND 1946 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET
1°09' 18 MILS
1° 20 MILS

SCALE 1:24,000
1 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 0 5 10 KILOMETER
1 MILE

Contour interval 20 feet
Datum is mean sea level

FOR SALE BY U.S. GEOLOGICAL SURVEY, WASHINGTON, D. C. 20242
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
Historical File
Topographic Division

Polyconic projection. 1927 North American datum
10000 foot grid based on Michigan (West)
rectangular coordinate system
1000-meter Universal Transverse Mercator grid ticks,
zone 16, shown in blue

MUGGUN CREEK, MICH.

N4715-W8830/7.5
1946
AMS 3278 I SE-SERIES V862

U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

MAY 17 1967

1755