



Maped by the Army Map Service
Published for civil use by the Geological Survey


Control by USC&GS, USCE, U. S. Lake Survey
and International Boundary Commission

U. S. topography from aerial photographs by photogrammetric
methods. Aerial photographs taken 1950. Field check 1951
Canadian topography from Army Survey Establishment, RCE,
dated 1953

Hydrography compiled from U. S. Lake Survey chart 62 (1955)

Polyconic projection. 1927 North American datum
10,000-foot grid based on Michigan coordinate system, east zone
1000-meter Universal Transverse Mercator grid ticks,
zone 16, shown in blue

Unchecked elevations are shown in brown



APPROXIMATE MEAN
DECLINATION, 1951

SCALE 1:62,500
3000 0 3000 6000 9000 12000 15000 18000 21000 FEET

1 5 0 1 2 3 4 5 KILOMETERS

CONTOUR INTERVAL 20 FEET IN THE UNITED STATES AND 25 FEET IN CANADA

DASHED LINES REPRESENT 10-FOOT CONTOURS

DATUM IS MEAN SEA LEVEL

DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS RIVER SURFACE AT
FOLLOWING STAGE: LAKE HURON 578 FEET

THE U. S. PORTION OF THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS

FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.

A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION

Medium-duty ——— Light-duty ———

Unimproved dirt ———



QUADRANGLE LOCATION

U. S. area also covered by 1:24,000 scale maps of
Baie de Wasai and Oak Ridge 7.5 minute quadrangles,
surveyed 1951.

LAKE GEORGE, MICH.

N 4615—W 8400/15

1951