

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

U. S. G. S.
FILE COPY
Inspection and Editing.

OREGON
SALEM 82 MI.
DETROIT 26 MI.
MCKENZIE BRIDGE QUADRANGLE



U. S. G. S.
FILE COPY
Inspection and Editing.

Topography by C.A. Stonesifer and
Linn County Cruiser Survey
Surveyed in 1933-1934

ROAD CLASSIFICATION
1947

Dependable hard-surface
Heavy-duty road
Secondary hard-surface
all-weather road
Dirt road

Dry weather roads
Loose-surface graded
Unsurfaced, graded
Dirt road

U. S. Route 18
State Route 20

More than two lanes indicated along road with tick at point of change

Scale 1:25,000

1 2 3 4 5 6 7 8 9 Miles

3000 1500 0 3000 6000 9000 12000 15000 18000 21000 24000 27000 Feet

1 2 3 4 5 6 Kilometers

Contour interval 100 feet
Datum is mean sea level

USCS
Historical
Topographic Division

Polyconic projection, 1927 North American datum
5000 yard grid based on U.S. zone system, G
20,000 foot grid based on Oregon (North) and
Oregon (South) rectangular coordinate systems

MCKENZIE BRIDGE, OREG.
Edition of 1940
reprinted 1948
N4400-W12200/30

U. S. G. S.
FILE COPY
Inspection and Editing.

MAR 19 1948