

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

UNITED STATES
DEPARTMENT OF THE ARMY
CORPS OF ENGINEERS

MAINE
SEBAGO LAKE QUADRANGLE
15-MINUTE SERIES



Topography by C. W. Nottage, W. D. Ingersoll,
R. S. Weaver, J. J. Consoli, L. E. Efrainson, H. Bloom,
F. C. Ebetsch, C. R. Mason, J. H. Knam, B. Housman,
R. Whittemore, R. R. Embrey, and F. H. Fatell
Surveyed in 1942

ROAD CLASSIFICATION
Heavy-duty ——— Light-duty ———
Medium-duty ——— Unimproved dirt ———

UTM GRID AND 1942 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET

SCALE 1:62500
3000 0 3000 6000 9000 12000 15000 18000 21000 FEET
1 5 0 1 2 3 4 5 KILOMETERS
CONTOUR INTERVAL 20 FEET
DATUM IS MEAN SEA LEVEL

Polyconic projection. 1927 North American datum
10,000-foot grid based on Maine (West)
rectangular coordinate system
1000-meter Universal Transverse Mercator grid ticks,
zone 19, shown in blue

SEBAGO LAKE, ME.

N 4345-W 7030/15

1942

AMS 6871 I-SERIES V711

COPY
REGULATION COMMISSION

DATE: