



Control by USGS and USC&GS

Polyconic projection. 1927 North American datum

Polyconic projection. 1927 North American datum

10,000-foot grid based on Illinois coordinate system, east zone
1000-meter Universal Transverse Mercator grid ticks

1000-meter Universal Transverse Mercator grid ticks,
zone 16, shown in blue

Red tint indicates areas in which only landmark buildings are shown.

Fine red dashed lines indicate selected fence and field lines which are generally visible on aerial photographs. This information is used

Revisions shown in purple compiled from aerial photographs taken

1977. Map edited 1978. This information not field checked

UTM GRID AND 1978 MAGNETIC NORTH
DECLINATION AT CENTER OF SHEET

3463 1 NW
SCALE 1:24 000

1 0 1000 2000 3000 4000 5000 6000 7000 FEET
1 0 5 10 KILOMETER

CONTOUR INTERVAL 5 FEET
NATIONAL GEODESIC SURVEY OF 1929

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092
AND BY THE STATE GEOLOGICAL SURVEY, URBANA, ILLINOIS 61801
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ILLINOIS

QUADRANGLE LOCATION

ROAD CLASSIFICATION

Light-duty

Unimproved dirt

Route U. S. Route State Route

USGS
Historical File
Topographic Division

DANVILLE SW, IL
N4000—W8737.5/7.5

1966
PHOTOREVISED 1978
AMS 3464 II SW—SERIES V863

DEC 18 1978

4100