



SEP 30 2000
USGS NWD
HISTORICAL MAP ARCHIVES



USGS
science for a changing world

Scale 1:250,000

0 5 10 15 20 Statute Miles

5 10 15 20 25 30 Kilometers

5 10 15 20 Nautical Miles

CONTOUR INTERVAL 200 FEET
WITH SUPPLEMENTARY CONTOURS AT 100 FOOT INTERVALS

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 17°W (310 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 17° (300 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, P.O. BOX 25296, DENVER, COLORADO 80225

A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

GRID ZONE DESIGNATION:
11S

30,000 M. SQUARE IDENTIFICATION

KQ	LQ	MQ
KP	LP	MP

(Note: The letters K, L, M are in the left column; Q, P, R are in the right column. The letters are in the same row as the letter to the left or right, or on the same line.)

IGNORE THE SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGEST figure of any grid number; example:

430000

TO GIVE A STANDARD REFERENCE TO THIS SHEET TO NEAREST 1000 METERS

SAMPLE POINT: BANGU

1. Read letters identifying 100,000 meter square in which the point lies;
2. Locate first VERTICAL grid line to the LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself;
3. Estimate tenths from grid line to point;
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself;
4. Estimate tenths from grid line to point.

SAMPLE REFERENCE:

If recording beyond 10° in any direction, prefix Grid Zone Designation, as:

11SP2474

RENO, NEVADA; CALIFORNIA
1957
REVISED 1971