MOBERLY

EDITION 3

NJ 15-2
SERIES V502

V502, EDITION 3

Prepared by the U.S. Army Topographic Command (KCSX), Washington, D.C. Compiled in 1955 by photogrammetric methods and from United States quadrangles, 1:62,500, 1920-51. Planimetry revised from aerial photographs taken 1950-52. Photographs field annotated 1954. Revised by the U.S. Geological Survey 1970.

Location of geodetic control established by government agencies is shown on corresponding 1:250,000-scale Geodetic Control Diagram

LEGEND

Figures in red denote approximate distances in miles between stars

POPULATED PLACES
- Over 500,000 — LOS ANGELES
- 100,000 to 500,000 — OMAHA
- 25,000 to 100,000 — GALVESTON
- 5,000 to 25,000 — Laramie
- 1,000 to 5,000 — Grand Coulee
- Less than 1,000 — Sun Valley

RAILROADS — Standard gauge — Single track — Double or Multiple — Narrow gauge

BOUNDARIES
- International
- State
- County
- Park or reservation

ROADS
- Primary, all-weather, hard surface
- Secondary, all-weather, hard surface
- Light-duty, all-weather, hard or improved surface
- Fair or dry weather, unimproved surface
- Trail
- Interchange
- Route markers: Interstate, U.S., State

Landplane airport
Landing area
Seaplane airport
Orchard
Woods-brushwood
Mine
Landmark: School; Church; Other
Spot elevation in feet
Marsh or swamp
Intermittent or dry stream
Power line

Scale 1:250,000

5 0 5 10 15 20 Statute Miles
5 0 5 10 15 20 25 30 Kilometers
5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 100 FEET
WITH SUPPLEMENTARY CONTOURS AT 50 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLACK NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 15

1970 MAGNETIC DECLINATION FROM TRUE NORTH VARIES FROM 7° (120 MILS) EASTERLY FOR THE CENTER OF THE WEST EDGE TO 5½° (100 MILS) EASTERLY FOR THE CENTER OF THE EAST EDGE

FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR WASHINGTON, D.C. 20242

LOCATION DIAGRAM



SECTIONIZED TOWNSHIP

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

TOWNSHIP OR RANGE LINE
LAND GRANT BOUNDARY

GRID ZONE DESIGNATION: 15S
100,000 M SQUARE IDENTIFICATION: VQ WQ VP WP
IGNORE the SMALLER figures of any grid number; these are for finding the full coordinates. Use ONLY the LARGER figure of the grid number, example: 4320000

TO GIVE A STANDARD REFERENCE ON THIS SHEET TO NEAREST 1000 METERS:
SAMPLE POINT: MUSSELFORK
1. Read letters identifying 100,000 meter square in which the point lies: WP
2. Locate first VERTICAL grid line to LEFT of point and read LARGE figure labeling the line either in the top or bottom margin, or on the line itself. Estimate tenths from grid line to point: 1
3. Locate first HORIZONTAL grid line BELOW point and read LARGE figure labeling the line either in the left or right margin, or on the line itself. Estimate tenths from grid line to point: 7
SAMPLE REFERENCE: WP1177
If reporting beyond 18° in any direction, prefix Grid Zone Designation, as: 15SWP1177

● INTERIOR—GEOLOGICAL SURVEY, WASHINGTON, D.C. — 1973

STOCK NO. V502XNJ152**03

NOV 1 1971

RETURN TO USGS RAD RESTON

MOBERLY, MISSOURI
1954
REVISED 1970