

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

U.S.G.S.
FILE COPY
Inspection and Editing.

VERMONT
HARDWICK QUADRANGLE



Topography by W. K. McKinley, C. W. Goodlove,
C. S. Wells, E. H. Cummings, E. C. Gartner, D. Landen,
S. S. Philbrick, and W. F. Witzgall
Control by U.S. Geological Survey
Surveyed in 1928 and 1934

ROAD CLASSIFICATION
1946
Dependable hard surface
Heavy-duty road
Secondary hard-surface
all-weather road
Dirt road
Dry weather roads
Loose-surface graded
Unsurfaced, graded
Dirt road
State Route
More than two lanes indicated along road with tick at point of change

U.S. Route

State Route

2 LANE, 4 LANE

Approximate mean declination

Scale 62500
1 inch = 1 mile
1000 500 0 1000 2000 3000 4000 5000 6000 7000 Yards
1000 500 0 1000 2000 3000 4000 5000 6000 7000 Feet
1 2 3 4 Miles
1 2 3 4 Kilometers
Contour interval 20 feet
Datum is mean sea level

Polyconic projection. North American datum
5000 yard grid based upon U.S. zone system. A
10000 foot grid based on Vermont
rectangular coordinate system

USGS
Historical File
Topographic Division
U.S.G.S.
FILE COPY
Inspection and Editing.

HARDWICK, VT.
Edition of 1938
reprinted 1947
N4430-W7215/15

HISTORICAL
MAY 8-1947

5425