



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Maped, edited, and published by the Geological Survey
Control by USGS and USC&GS

Topography by plane-table surveys 1943. Culture and drainage revised from aerial photographs taken 1954. Field check 1956. Hydrography compiled from USC&GS charts 868 (1953) and 1263 (1955)

Polyconic projection. 1927 North American datum 10,000-foot grid based on Florida coordinate system, north zone 1000-meter Universal Transverse Mercator grid ticks, zone 16, shown in blue

35°
TRUE NORTH
MAGNETIC NORTH

APPROXIMATE MEAN
DECLINATION, 1956

SCALE 1:24000

1 0 1000 2000 3000 4000 5000 6000 7000 FEET

1 0 1 2 3 4 5 6 7 8 9 10 KILOMETER

CONTOUR INTERVAL 10 FEET
DATUM IS MEAN SEA LEVEL
DEPTH CURVES AND SOUNDINGS IN FEET—DATUM IS MEAN LOW WATER
SHORELINE SHOWN REPRESENTS THE APPROXIMATE LINE OF MEAN HIGH WATER
THE AVERAGE RANGE OF TIDE IS APPROXIMATELY 1 FOOT

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

USGS
Historical File
Topographic

QUADRANGLE LOCATION

FLORIDA

ROAD CLASSIFICATION

Medium-duty ——— Light-duty ———
Unimproved dirt ———
U. S. Route ——— State Route ———

U.S.G.S.
FILE COPY
TOPOGRAPHIC DIVISION

LONG POINT, FLA.
N3000-W8530/7.5
1956

MAY 11 1952

2580