



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

STATE OF FLORIDA

MC INTYRE QUADRANGLE
FLORIDA
7.5 MINUTE SERIES ORTHOPHOTOMAP
(TOPOGRAPHIC - BATHYMETRIC)



CONVERSION
SCALES




Feet	Meters
1	3048
2	6096
3	9144
4	12192
5	15240
6	18288
7	21336
8	24384
9	27432
10	30480

To convert feet to meters
multiply by 3.048


To convert meters to feet
multiply by 3.2808

1. Dryland
2. Wetlands (May be partially submerged at mean high tide)
3. Exposed at mean low tide




Produced by the United States Geological Survey
and the National Ocean Survey
Control by USGS and NOS/NOAA
Orthophotomap prepared from aerial photograph taken
January 10, 1976. Topography by photogrammetric methods
from aerial photographs taken January 1975
Field checked 1976. Map edited 1982
Supersedes topographic map dated 1945
Bathymetry compiled by the National Ocean Survey from
tide-coordinated hydrographic surveys
Soundings compiled from NOS chart 11405
This information is not intended for navigational purposes
Mean low water (dotted) line and mean high water (solid) line
compiled by NOS from tide-coordinated aerial photographs
Apparent shoreline (outer edge of vegetation) shown
by photomicroscopy
Projection and 10,000-foot grid ticks: Florida coordinate
system, north zone (Lambert conformal conic)
1000-meter Universal Transverse Mercator grid, zone 16
1927 North American Datum
The difference between 1927 North American Datum and North
American Datum of 1983 (NAD 83) for 7.5-minute intersections
is given in USGS bulletin 1875. The NAD 83 is shown by
dashed corner ticks
Dotted land lines established by private subdivision
of the Forbes Purchase
There may be private inholdings within the boundaries of
the National or State reservations shown on this map

Photoinspected from 1989 source; no major culture or
drainage changes observed. Boundaries and names revised 1992




Survey Number	Survey Date	Survey Scale	Survey Line Spacing (Inch, Miles)
H-5867	1935	1:20,000	0.2-1.5



CONTOUR INTERVAL 2 METERS
SUPPLEMENTARY CONTOUR INTERVAL 1 METER
NATIONAL GEODETIC VERTICAL DATUM OF 1929
CONTROL ELEVATIONS SHOWN TO THE NEAREST 0.1 METER
OTHER ELEVATIONS SHOWN TO THE NEAREST 0.5 METER
BATHYMETRIC CONTOUR INTERVAL 1 METER WITH SUPPLEMENTARY
0.5 METER CONTOURS—GULF COAST LOW WATER DATUM
THE RELATIONSHIP BETWEEN THE TWO DATUMS IS VARIABLE
THE MEAN RANGE OF TIDE IS APPROXIMATELY 0.8 METERS

BASE MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
BATHYMETRIC SURVEY DATA COMPLIES WITH INTERNATIONAL HYDROGRAPHIC
ORGANIZATION (IHO) SPECIAL PUBLICATION 44 ACCURACY STANDARDS
AND/OR STANDARDS USED AT THE DATE OF THE SURVEY
FOR SALE BY U.S. GEOLOGICAL SURVEY, DENVER, COLORADO 80225, OR RESTON, VIRGINIA 22092
AND NATIONAL OCEAN SERVICE, ROCKVILLE, MARYLAND 20852
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST



ROAD CLASSIFICATION

Primary highway,
hard surface

Secondary highway,
hard surface

Trails

Interstate Route

U. S. Route

State Route

County Route

Light-duty road, hard or
improved surface

Unimproved road

CONTOURS AND ELEVATIONS
IN METERS

MC INTYRE, FLA.
29084H5-TB-024
1982
MINOR REVISION 1992
DMA 4043 1 NE-SERIES V8470

