




Mapped and edited by Tennessee Valley Authority
Published by the Geological Survey
Control by USC&GS, USGS, USED, and TVA
Topography by USGS and TVA by multiplex methods from aerial
photographs taken 1948. Field examination by TVA, 1950
Polyconic projection. 1927 North American datum
10,000-foot grid based on Alabama (West) and
Mississippi (East) rectangular coordinate systems

TRUE NORTH
MAGNETIC NORTH
APPROXIMATE MEAN
DECLINATION 1950



CONTOUR INTERVAL 20 FEET
DASHED LINES REPRESENT HALF-INTERVAL CONTOURS
DATUM IS MEAN SEA LEVEL

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, WASHINGTON 25, D. C.
AND BY U. S. TENNESSEE VALLEY AUTHORITY, CHATTANOOGA OR KNOXVILLE, TENN.
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

ROAD CLASSIFICATION
HARD-SURFACE ALL WEATHER ROADS DRY WEATHER ROADS
Heavy-duty — 1 LANE 18 LANE Improved dirt —
Medium-duty — 1 LANE 18 LANE Unimproved dirt —
Loose-surface, graded, or narrow hard-surface —
U. S. Route State Route

BISHOP, ALA.-MISS.
N3437.5-W8800/7.5

PRINTED 1951

U. S. GEOLOGICAL SURVEY
WASHINGTON
NOV 15 1951
LIBRARY