



POPULATED PLACES

Over 500,000 _____

100,000 to 500,000 _____

25,000 to 100,000 _____

5,000 to 25,000 _____

1,000 to 5,000 _____

Less than 1,000 _____

RAILROADS

Standard gauge _____ Single-track

Narrow gauge _____

BOUNDARIES

International _____

State _____

County _____

Park or reservation _____

LEGEND

ROAD DATA 1953
Figures in red denote approximate distances in miles between stars

ROADS
Hard surface, heavy duty
More than two lanes wide

3 LANES 1 LANE

ROADS
Two lanes wide; Federal route marker
Spot surface, medium duty
More than two lanes wide

3 LANES 1 LANE

ROADS
More than two lanes wide; State route marker
Improved light dirt
Unimproved dirt

10

Trail

Landmarks: School; Church; Other

Horizontal control point

Spot elevation in feet

Marsh or swamp

Intermittent or dry stream

Power line

Double or Multiple

Landplane airport

Landing area

Seaplane airport

Seaplane anchorage

Woods/bushwood

Scale 1:250,000

5 0 5 10 15 20 Statute Miles
5 0 5 10 15 20 25 30 Kilometers
5 0 5 10 15 Nautical Miles

CONTOUR INTERVAL 50 FEET
WITH SUPPLEMENTARY CONTOURS AT 25 FOOT INTERVALS

TRANSVERSE MERCATOR PROJECTION

BLUE NUMBERED LINES INDICATE THE 10,000 METER UNIVERSAL TRANSVERSE MERCATOR GRID, ZONE 15
THE LAST FOUR DIGITS OF THE GRID NUMBERS ARE OMITTED.

1955 MAGNETIC DECLINATION FOR THIS SHEET VARIES FROM 6°30' EASTERLY FOR THE CENTER OF THE WEST EDGE TO 4°15' EASTERLY FOR THE CENTER OF THE EAST EDGE. MEAN ANNUAL CHANGE IS 0°02' WESTERLY.

USERS NOTING ERRORS OR OMISSIONS ON THIS MAP ARE URGED TO MARK HEREON AND FORWARD DIRECTLY TO COMMANDING OFFICERS, ARMY MAP SERVICE, WASHINGTON, D.C. MAPS SO FORWARDED WILL BE RETURNED OR REPLIED IF DESIRED.

[illegible]

United States. Topo. 1:250,000.
sheet *Stillwater*,
cop. *1.*

PRINTED BY ARMY MAP SERVICE CORPS OF ENGINEERS, 5-58 7796262

GPO ZONE DESIGNATION: 157

100,000 M. SQUARE IDENTIFICATION

LOCATOR

V	WA	VA
W	W	8
V	W	1

50

RENDER THE SMALLER FIGURES of grid number: these are for finding the full coordinates, use ONLY the ARMSER figures of the grid number example:

4930000

TO GIVE A STANDARD REFERENCE ON THE SHEET TO MEASURE DISTANCES

SAMPLE POINT: COOR LINE

1. Read letters identifying 100,000 meter square in which the point is located.
2. Locate from VERTICAL and grid below the line either on the top or below the line on the line itself.
3. Locate from HORIZONTAL and grid to the line either on the left or right of the line on the line itself.
4. Read distance results from 100,000 meter square.

SAMPLE REFERENCE: VAB887

IF reporting beyond 10" in any direction, prefix GPO Zone Designation as: 157VAB887