

778 IV
(SILVER BAY 1:62,500)



Maped, edited, and published by the Geological Survey
Control by USGS and USCGS
Topography from aerial photographs by Kelsh plotter
Aerial photographs taken 1953. Field check 1956
Hydrography compiled from U. S. Lake Survey chart 96 (1955)
Polyconic projection. 1927 North American datum
10,000-foot grid based on Minnesota coordinate system, north zone
1000-meter Universal Transverse Mercator grid ticks,
zone 15, shown in blue
Dashed land lines indicate approximate locations
Unchecked elevations are shown in brown

Map photoinspected 1976
No major culture or drainage changes observed

SCALE 1:24,000

CONTOUR INTERVAL 10 FEET
NATIONAL GEODETIC VERTICAL DATUM OF 1929
DEPTHS CURVES AND SOUNDINGS IN FEET—DATUM IS 601 FEET

THIS MAP COMPLIES WITH NATIONAL MAP ACCURACY STANDARDS
FOR SALE BY U. S. GEOLOGICAL SURVEY, RESTON, VIRGINIA 22092
A FOLDER DESCRIBING TOPOGRAPHIC MAPS AND SYMBOLS IS AVAILABLE ON REQUEST

To place on the predicted North American Datum 1983
move the projection lines 6 meters north and
12 meters east as shown by dashed corner ticks
There may be private inholdings within the boundaries of
the National or State reservations shown on this map

ROAD CLASSIFICATION

Heavy-duty ——— Light-duty ———
Unimproved dirt ———
U. S. Route

SPLIT ROCK POINT, MINN.
NW/4 SPLIT ROCK POINT 15' QUADRANGLE
N 4707.5—W 9122.5/7.5

1956
PHOTOINSPECTED 1976
AMS 778 III NW—SERIES V872

MAP AND AIR PHOTO
LIBRARY

JAN 20 1983

University of Wisconsin
Madison